



FLEX UNITS

-- 4 " --
 -- 5 " --
 -- 6 " --
 -- 8 " --
 -- 10 " --
 -- 12 " --
 -- 15 " --

-- DIMENSIONS

-- PRICELIST

-- ORDERFORM

C-QUENZE

PROFILE

NEWS

FAQ

GALLERY

PARTNERS

LINKS

SIMULATOR

WALLPAPER

HOME

SANDWICH CONE

Flexunits 10 C 77 25 10 KAP

| | |
|--------------------------|---------------------|
| Effective Cone Area | 334 Cm ² |
| Nominal Impedance | 8 Ohm |
| Resonance Frequency | 25 Hz |
| Equivalent Air Volume | 110 Ltrs. |
| Mecanical Q Factor | 6 |
| Electrical Q Factor | 0,25 |
| Total Q Factor | 0,24 |
| Acceleration Factor | 257 |
| Nominal Power Handling | 200 W |
| Efficiency | 90 dB |
| Frequency response | 34 - 1.500 Hz |
| DC resistance | 5.4 Ohm |
| Compliance | 0,699 mm/Nm |
| Mechanical res. | 1,52 Ns/m |
| VC inductance | 0.9 mH |
| Moving mass | 54,5 g |
| Force factor | 14 N/A |
| Linear excursion (x-max) | 8.6 mm |
| Max. excursion (P-P) | 42 mm |



Frequency response

On it's way

